

TECHNICAL DATA SHEET

9.575.1

Applications



CYCLIC



SOLAR



MARINE

PHYSICAL CHARACTERISTICS


	SI Units	US Units
Length	353 mm	13.9 inch
Width	175 mm	6.9 inch
Height	190 mm	7.5 inch
Typical weight	24.0 kg	52.9 lbs

Specifications :

- Nominal voltage: 12 V
- Rated capacity: 90 Ah (at C₂₀ and 30 °C)
- Plate technology: Calcium / Calcium
- Separator: Polyethylene + glass mat
- Electrolyte: Sulphuric acid; analytical grade
- Standards: IEC 60254; IEC 61427
- Case / Lid material: Polypropylene
- Lid type: Kamina
- Terminal type: Top / Automotive
- Carrying Handles: Available
- Cycles at 50% DoD: up to 400 cycles
- PVES applications: up to 800 cycles

Performance characteristics:

BATTERY DISCHARGE PERFORMANCE AT 25°C							
Discharge rate		C ₅ (5 h)	C ₂₀ (20 h)	C ₁₀₀ (100 h)	Capacity at 25 A		
End of discharge voltage		10.20 V	10.50 V	10.80 V	10.50 V		
Discharge capacity		75 Ah	90 Ah	100 Ah	160 min		
Temperature correction factor of discharge C ₅ (5 h) capacity							
Temperature	-10 °C	0 °C	20 °C	25 °C	30 °C	35 °C	40 °C
Correction factor	0.76	0.82	0.94	0.97	1.00	1.03	1.06



It is mandatory to check the electrolyte level every 3 months and top up with deionized water to the markings.