

# TECHNICAL DATA SHEET

## DGY12-40D



### Applications



**CYCLIC**



**STATIONARY**



**SOLAR**



**MARINE**

### Specifications

#### PERFORMANCES

Voltage (V):	12 V	
C20 (Ah):	40.0	20 h
Rc (min):	0	
Cranking (A):	280	EN
Vibration:	V3 (35Hz/6g/20h)	
Endurance:	200 cycles@100%	
Charge:	CHARGED	
Technology:	GEL	
Grid:	Ca/Ca	

Type:	LB1	BLACK
Hold Down:	B4	
H.D. Adapter:	No	

#### CONTAINER

#### COVER

Type:	DIN	BLACK
Polarity:	ETN 0	
Terminals:	EN full Ford lug	
Terminal Adapter:	No	
SOCI:	No	
Ventilation:	Independent	
Filter:	No	
Lateral Plug:	No	

#### WEIGHT AND STD. DIMENSIONS

Battery Weight (kg ± 5%):	15.0
Volume acid (l ± 5%):	3.0
Length (mm ± 2):	207
Width (mm ± 2):	175
Height (mm ± 2):	175

#### PLUGS

Type:	6 x M18 Valve	GREY MEDIUM
-------	---------------	-------------

#### HANDLES

Type:	None
-------	------

#### OTHERS

Degassing Tube:	No
-----------------	----

### Dimensions

