

TECHNICAL DATA SHEET

DGY12-120D

Applications



CYCLIC



STATIONARY



SOLAR



MARINE

Specifications

PERFORMANCES

Voltage (V):	12 V	
C20 (Ah):	110.0	20 h
Rc (min):	0	
Cranking (A):	760	EN
Vibration:	V3 (35Hz/6g/20h)	
Endurance:	200 cycles@100%	
Charge:	CHARGED	
Technology:	GEL	
Grid:	Ca/Ca	

CONTAINER

Type:	D07	BLACK
Hold Down:	B0	
H.D. Adapter:	No	

COVER

Type:	Flat/Screw	BLACK
Polarity:	ETN 2	
Terminals:	EN taper post	
Terminal Adapter:	No	
SOCI:	No	
Ventilation:	Independent	
Filter:	No	
Lateral Plug:	No	

WEIGHT AND STD. DIMENSIONS

Battery Weight (kg $\pm$ 5%):	37.5
Volume acid (l $\pm$ 5%):	9.1
Length (mm $\pm$ 2):	286
Width (mm $\pm$ 2):	269
Height (mm $\pm$ 2):	230

PLUGS

Type:	6 x M18 Valve	GREY MEDIUM
-------	---------------	-------------

HANDLES

Type:	2 x Rope (Rigid hol	BLACK
-------	---------------------	-------

OTHERS

Degassing Tube:	No
Gel	

Dimensions

